

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number: WO 98/1693	36
G21F 5/005	A1	(43) International Publication Date: 23 April 1998 (23.04.5	98)
(21) International Application Number: PCT/SE  (22) International Filing Date: 3 October 1997 (		DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE)	
(30) Priority Data: 9603757-7 15 October 1996 (15.10.96)	\$	Published  With international search report.  In English translation (filed in Swedish).	
(71)(72) Applicant and Inventor: JOHANSSON, Gert Kohlswa Gjuteri AB, P.O. Box 101, S-730 30 Kol	sva (SI	В).	
(74) Agent: BERGGREN, Björn; Långrevsgatan 1, S Västerås (SE).	:-723 ·	49	

## (54) Title: METHOD OF MANUFACTURING OBLONG CAPSULES

#### (57) Abstract

The present invention relates to a method of manufacturing oblong canisters for storing spent nuclear fuel elements. This method is characterized in that a bundle of tubes (2) the length of the canister are joined together to form a parcel, by means of welding for instance, around which parcel a casing (9) of metal is cast.



## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

ΛL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	Prance	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaljan	GB	United Kingdom	MC	Monaco	TD	Chad
	Bosnia and Herzegovina	CR CD	Georgia	MD	Republic of Moldova	TG	Togo
BA	•	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BB	Barbados	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BE	Belgium Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BF		HU	Hungary	MŁ	Mali	TT	Trinidad and Tobago
BG	Bulgaria	IE	Ireland	MN	Mongolia	UA	Ukraine
BJ	Benin December	IL	Israel	MR	Mauritania	UG	Uganda
BR	Brazil	IS	Iceland	MW	Malawi	US	United States of America
BY	Belarus	it	Italy	MX	Mexico	UZ	Uzbekistan
CA	Canada	JР	Japan	NB	Niger	VN	Viet Nam
CF	Central African Republic	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CG	Congo	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CH	Switzerland	KP	Democratic People's	NZ	New Zcaland		
Cl	Côte d'Ivoire	N.F	Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ.	Kazakstan	RO	Romania		
CU	Cuba	I.C	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	u	Liechtenstein	SD	Sudan		
DE	Germany			SE	Sweden		
DK	Denmark	LK	Sri Lanka	SG	Singapore		•
EE	Estonia	LR	Liberia	30	Ombuhoro		

5

Method of manufacturing oblong capsules.

#### Technical field:

The present invention relates to a method of manufacturing oblong canisters for storing spent nuclear fuel elements.

#### Background art:

Casting long objects with internal cavities while retaining the straightness of the cavities is problematical. This applies particularly to canisters for storing spent nuclear fuel elements. When complete such canisters shall be sealed at the ends and surrounded by an outer casing of copper. This is a method known per se, but it is important that the cavities in the canisters are straight. Furthermore, the casting may not be too complicated and thus expensive.

15

20

#### Description of the invention:

The method according to the invention aims at solving these problems and is characterised in that a bundle of tubes the length of the canister are joined together to form a parcel around which a casing of metal is cast. According to this method sand cores or other types of nuclear material are replaced when the cavities are cast. Straight cavities are obtained in a simple and efficient manner. Tubes having square or round cross section or tubes of some other cross section may be used in the parcel to be joined together, by welding for instance.

25

30

35

In a suitable embodiment, for instance, twelve square tubes are used which are joined together and fixed in the desired grouping, by welding for instance, or bracing between the tubes, after which the tube parcel is filled with filler as required, e.g. ladle lining, and pre-heated. The pre-heated tube parcel is placed in the lower part of a casting mould and the other parts of the mould are positioned, after which casting of the casing is performed in vertical position, or horizontal position if its size permits, and with casting gates at different levels, for instance. The metal used is steel SS 1306, for instance, or some other material. The canister shall be long, having a length:diameter ratio of between 3:1 and

6:1, but other ratios are also possible. Equipment can be built for extreme proportions.

One advantage with the method is that strict straightness tolerances or other tolerances for the canister can be obtained and, of course, that the canister can be produced at all. The requirement (in the case of square tubes) may be that a gauge with dimensions 153:153:4500 shall be passed through the cavity of the canister.

10 The finished canister shall primarily be used for storing spent nuclear fuel elements or other material and shall be sealed all around and at the ends in known manner with an outer casing of copper.

## Brief description of the drawings:

15 The method according to the invention is exemplified in the accompanying drawings. Figure 1 shows a longitudinal section of a canister to be cast and Figure 2 shows the same canister in cross section. Figure 3 shows a cross section through a parcel of square tubes.

### 20 Description of embodiment:

Figures 1 and 2 show a finished canister, in this case a parcel of twelve square tubes (2) which have been welded together to a parcel and filled with filler, after which pre-heating may be performed if necessary. The ratio between the canister length (L) and its diameter (D) is here 4.9:1.

When the fuel elements have been placed in the canister it shall be surrounded by an outer casing of copper (1) and end pieces of the same material.

The welded parcel of tubes (Figures 1 and 2) is placed upright and fixed in the lower part or core of a casting mould. The other parts of the mould are positioned and the casting in steel is performed in vertical or horizontal position, e.g. through casting gates at different levels. The material of the tubes is normally steel, SS 1312, and the casting is performed in steel with a wall thickness of 10 mm. When the casting body has cooled the ladle lining is emptied out. One or more casting

PCT/SE97/01658

gates can be used at one or more levels, determined by casting weight, dimensions, etc.

Figure 3 shows the square tubes and the straight cavities (2) with bracing (5) welded between the tubes (2). After insertion of the elements the canister is enclosed in copper in known manner.

The method according to the invention can be varied in many ways within the scope of the following claims.


10


10

#### CLAIMS

- 1. A method of manufacturing an oblong canister for storing spent nuclear fuel elements, characterized in that a bundle of tubes (2) the length of the canister are joined together to form a parcel around which a casing (9) of metal is cast.
- 2. A method as claimed in claim 1, characterized in that a number of tubes (2) are welded together as bracing (5) between the tubes, after which the parcel of tubes is filled with filler, e.g. ladle lining, and pre-heated if necessary.
- 3. A method as claimed in claim 2, characterized in that the pre-heated tube parcel is secured in the lower part of a casting mould and the other parts are positioned, after which casting of the casing is performed in vertical position.
  - 4. A method as claimed in claims 1-3, characterized in that the welded parcel (2) consists of a number of square tubes.
  - 5. A method as claimed in any of the preceding claims, characterized in that the tubes are straight and/or parallel with each other.
- 25 6. A method as claimed in claims 1-3, characterized in that the casting is performed at different levels.
  - 7. A method as claimed in any of the preceding claims, characterized in that the casing (9) consists of steel SS 1306.

20





#### INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01658

A. CLASSIFICATION OF SUBJECT MATTER		
IPC6: G21F 5/005 According to International Patent Classification (IPC) or to be	th national classification and IPC	
B. FIELDS SEARCHED		
Minimum documentation searched (classification system follow	ed by classification symbols)	
IPC6: G21F, B22D, C23C		
Documentation searched other than minimum documentation t	the extent that such documents are included i	n the fields searched
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (	name of data base and, where practicable, scarci	n terms used)
WPI		
C. DOCUMENTS CONSIDERED TO BE RELEVAN	lT .	
Category* Citation of document, with indication, where	appropriate, of the relevant passages	Relevant to claim No.
A WO 9526030 A1 (TRANSNUCLEAIRE (28.09.95), figures 1-4,		1-7
<del></del>		
A DE 3140020 A1 (KERNFORSCHUNGS GMBH), 21 April 1983 (21.	ZENTRUM KARLSRUHE 04.83), figures 1,2,	1-7
abstract		
A WO 9526029 A1 (TRANSNUCLEAIRE (28.09.95), figure 1, abs		1-7
		·
A US 5550882 A (LEHNERT ET AL), (27.08.96), figure 1, abs		1-7
Further documents are listed in the continuation of	Box C. X See patent family annex	
Special categories of cited documents:  "A" document defining the general state of the art which is not consider the forest of the second	tater document published after the inte date and not in conflict with the applic the principle or theory underlying the i	ation but cited to understand
to be of particular relevance  "E" ertier document but published on or after the international filling d  "L" document which may throw doubts on priority claim(s) or which is	te "X" document of particular relevance: the considered novel or cannot be considered step when the document is taken alone	
cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance: the	claimed invention cannot be
"O" document referring to an oral disclosure, use, exhibition or other means	considered to involve an inventive step combined with one or more other such being obvious to a person skilled in the	documents, such combination
"P" document published prior to the international filing date but later the priority date claimed	"&" document member of the same patent	
Date of the actual completion of the international search	Date of mailing of the international se	earch report
	0 4 -02- 18	998
14 January 1998	A distant	
Name and mailing address of the ISA/	Authorized officer	
Swedish Patent Office Box 5055, S-102 42 STOCKHOLM	Tomas Lund	
Facsimile No. +46 8 666 02 86	Telephone No. +46 8 782 25 00	

Form PCT/ISA/210 (second sheet) (July 1992)

# INTERNATIONAL SEARCH REPORT Information on patent family members

02/12/97

International application No. PCT/SE 97/01658

Patent document cited in search report		Publication date	Patent family member(s)			Publication date	
10	9526030		28/09/95	DE	663706	T	02/05/96
,,,	302000		,,	DE	69500741		00/00/00
			,	EP	0663706	A,B	19/07/95
				EP	0752151	A	08/01/97
				ES	2079340	T	16/01/96
				FR	2715004	A,B	13/07/95
				JP	7235349	A	05/09/95
				US	5611707	A	18/03/97
				ZA	9502084	Α	12/03/96
DE	3140020	A1	21/04/83	FR	2514545	A,B	15/04/83
_	41,001			GB	2109984	A,B	08/06/83
				JР	58072100	Α	28/04/83
√O	9526029	A1	28/09/95	CZ	9602744	A	15/01/97
,,	3020023		<b></b> ,,	EP	0752150	A	08/01/97
				FR	2717945	A,B	29/09/95
				ZA	9502420	A	16/01/96
JS	5550882	A	27/08/96	AU	7972694	A	04/05/95
				CN	1117322	A	21/02/96
				EP	0673541	A	27/09/95
				FI	952817	A	08/06/95
				JP	850738 <i>2</i>		06/08/96
				US	5438597		01/08/95
				WO	9510838		20/04/95
				ZA	9407869	A	09/04/96